



## **Fulton Mill Service Co.**

@ North Star BlueScope Steel  
6565 County Road 9  
Delta, OH 43515

### **Materials and Usage Guide Steel Slag Aggregates**

<b>Item#</b>	<b>Description</b>	<b>Base</b>	<b>Fill</b>	<b>Fill (Soft Ground)</b>	<b>Secondary Roads (Gravel)</b>	<b>Landscaping</b>	<b>Pipe Bedding</b>
2600	Duraberm 1's and 2's (3 x ¾)	X	X	X	X	X	
2189	2 x 0 Duraberm	X	X	X	X	X	
2188	1 x 0 Duraberm	X	X	X	X	X	
80	EAf Steel Slag Sand (1/8 x 0)		X	X		X	X
76	8's (1/2 x 1/8) Steel Slag		X	X		X	X
926	57's (1 x ½) Steel Slag		X	X		X	X

\*\*Typically, Duraberm products are not recommended for confined applications. However, when blended at a ratio of 50% or less and when applied appropriately, Duraberm products have the potential to be used in confined spaces, under buildings and/or under paved roads. Please talk to your local salesperson for more information.

#### **For More Information, Please Contact:**

Contractor / Michigan Sales: Kurt Crowel – (219) 406-1194

Email: [kcrowel@levyco.net](mailto:kcrowel@levyco.net)

Residential Sales: Michelle Hutchins – (260) 438-7743

Email: [mhutchins@levyco.net](mailto:mhutchins@levyco.net)

Plant (Office): 419-822-8286

Plant (Fax): 419-822-3729